

Photo by Sascha Bosshard on Unsplash

Mathematical Foundations

Loop invariants

CS51 – Fall 2025

Proving correctness of iterative algorithms

- Iterative algorithms: algorithms that use loops, such as for and while loops.
- What do we mean by our iterative program being correct?
  - if certain conditions are met and we run the program, then the program will terminate (we say that the program will halt) and we will receive the correct result.
- The condition that needs to be met to run the program is called a **precondition**.
- The result that needs to be met after the program **termination** is called a **postcondition**.
- The precondition and postcondition are known as the **specifications** of the program.

Proving correctness of iterative algorithms

- To prove the correctness of a program we would need to prove that if the precondition is true, then the program will terminate and the postcondition will be true.
- If we were to think of this in terms of logic, we would need to prove that
  - precondition ⇒ termination ∧ postcondition
- Sometimes, it makes sense to break down the proof in two parts:
  - Proving *termination*: precondition ⇒ termination
  - Proving *partial correctness*: precondition ∧ termination⇒ postcondition

Practice Time

- Write an iterative function called `iterative_multiplication` that computes and returns the product of two non-negative integers m and n via repeated addition.
- What are the pre- and post-conditions?

Answer

```
def iterative_multiplication(m, n):
    product = 0
    for i in range(n):
        product += m
    return product
```

```
def iterative_multiplication(m, n):
    product = 0
    i=0
    while i<=n:
        product += m
        i += 1
    return product
```

- pre-condition: the input variables m and n are non-negative integers.
- post-condition: the returned value is equal to the product of m and n.

Is our output correct?

- To show that the output is correct we would need to know that the returned product is indeed equal to m*n
- We will do so by using **loop invariants** and assume that while loops are in the form of:

```
while (guard):
        #body
```

- And for loops are in the form of:

```
for i in range (start, stop, step): #start=0, step=1 by default
        #body
```

Loop invariants

- Assuming the precondition holds, a loop invariant for a loop is a condition that is true at the beginning and end of every iteration of a loop.
- To prove correctness, we need to show:
  - *Initialization*: The loop invariant is true before the loop runs for the first iteration.
  - *Maintenance*: We assume that the loop invariant is true before an iteration. Given this assumption we need to show that the loop invariant remains true after the execution of the loop body and before entering the next iteration.
  - *Postcondition*: Show that if the guard fails/is false (so the loop exits), then the desired result of the loop has been achieved: the loop post-condition holds.
  - *Termination*: After a finite number of iterations of the loop, the guard will become false and the loop will terminate.
- All four step would be necessary to show full correctness.

Iterative multiplication - Loop invariant

- Loop invariants, often make a statement depending on an index i and what you have seen so far, e.g., after i iterations, product = m x i.

Iterative multiplication - Initialization

- *Initialization*: Before the first iteration product=0 and i=0, thus product=0=mx0.
- So the loop invariant holds before the first iteration.

```
def iterative_multiplication(m, n):
    product = 0
    for i in range(n):
        product += m
    return product
```

```
def iterative_multiplication(m, n):
    product = 0
    i=0
    while i < n:
        product += m
        i += 1
    return product
```

Iterative multiplication - Maintenance

- *Maintenance*: Let's assume the loop invariant is true at the start of the i-th iteration of the loop, that is product = m x i.
- In the loop body, we execute product = product + m and increment i by 1.
- After this iteration, $product_{new} = (m \times i) + m = m \times (i+1) = m \times i_{new}$.
- So the invariant still holds.

```
def iterative_multiplication(m, n):

    product = 0

    for i in range(n):

        product += m

    return product
```

```
def iterative_multiplication(m, n):
    product = 0
    i=0
    while i<n:
        product += m
        i += 1
    return product
```

Loop invariant for linear search - Postcondition

- *Postcondition:* The loop terminates when the guard fails, that is when i = n.
- By the loop invariant product = m x i = m x n.
- Which is the exact result we were hoping to compute!

```
def iterative_multiplication(m, n):
    product = 0
    for i in range(n):
        product += m
    return product
```

```
def iterative_multiplication(m, n):
    product = 0
    i=0
    while i<n:
        product += m
        i += 1
    return product
```

Loop invariant for linear search - Termination

- *Termination*: Since i starts at 0, increases by 1 at each iteration, and the loop guard is i < n, the loop must terminate after exactly n iterations.
- Thus, in a finite number of iterations of the loop, we will calculate the product of m and n.
- Putting it altogether, we have proven the correctness of this program.

```
def iterative_multiplication(m, n):
    product = 0
    for i in range(n):
        product += m
    return product
```

```
def iterative_multiplication(m, n):
    product = 0
    i=0
    while i<n:
        product += m
        i += 1
    return product
```

Practice time

- You are given the following program that tests whether a positive integer is prime by iterating through all numbers from 2 to $\sqrt{n}$ and checking divisibility.
- First, test it with a few numbers.
- What are the pre-and post-conditions? What is a good loop invariant?
- Use loop invariants to prove that the function works correctly.

```
def is_prime(n):
    i = 2
    while i * i <= n:
        if n % i == 0:
            return False
        i += 1
    return True
```

Answer

- Pre-condition : Input n is an integer, $n \geq 2$.
- Post-condition: The function returns True if n is prime and False if it is composite.
- Loop invariant: At the start of each iteration i, no integer k with $2 \leq k < i$ divides n.

```
def is_prime(n):
    i = 2
    while i * i <= n:
        if n % i == 0:
            return False
        i += 1
    return True
```

Answer

- *Initialization*: At the start of the first loop, i=2. There are no integers k with $2 \leq k < 2$, so the invariant is trivially true.

```
def is_prime(n):
    i = 2
    while i * i <= n:
        if n % i == 0:
            return False
        i += 1
    return True
```

Answer

- *Maintenance*: Suppose at the start of some iteration the invariant holds and no integer k with $2 \leq k < i$ divides n.
  - Once we enter the loop, if `n % i == 0`, then we return False immediately, which is correct because n would be a composite if it can be divided by i.
  - Otherwise, `n % i != 0`. That means i does not divide n.
  - Then we increment `i` by `1` to `i+1`.
  - Thus at the start of the next iteration, no integer k with $2 \leq k < (i+1)$ divides n. The invariant holds.

```
def is_prime(n):
    i = 2
    while i * i <= n:
        if n % i == 0:
            return False
        i += 1
    return True
```

Answer

- *Post-condition*: The loop exits when i*i>n. At this point, every possible divisor between 2 and $\sqrt{n}$ has been checked.
- If any such divisor existed, the loop would have terminated earlier and returned False.
- Since it did not, no divisor exists up to $\sqrt{n}$, so n must be prime. Therefore, the postcondition holds when the loop terminates and returns True.

```
def is_prime(n):
    i = 2
    while i * i <= n:
        if n % i == 0:
            return False
        i += 1
    return True
```

Answer

- *Termination*: The variable i starts at 2 and increases by 1 each iteration. The guard i * i <= n eventually becomes False when i > $\sqrt{n}$. Thus, the loop always terminates.

```
def is_prime(n):
    i = 2
    while i * i <= n:
        if n % i == 0:
            return False
        i += 1
    return True
```

Practice time

- Write an iterative function count_digits, that given a (decimal) number it returns how many digits it has. For example,
- count_digits(7) → 1
- count_digits(123) → 3
- count_digits(10005) → 5
- What are the pre-and post-conditions? What is a good loop invariant?
- Use loop invariants to prove that the function works correctly.

Answer

- Pre-condition : Input n is an integer, n > 0.
- Post-condition: The function returns the number of digits in the decimal representation of n.
- Loop invariant: after count iterations, the last count digits have been removed from the original n and n is the part of the original number that remains to be processed.

```
def count_digits(n):
    count = 0
    while n > 0:
        n //= 10
    count += 1
    return count
```

Answer

- *Initialization*: At the start of the first loop, count=0 and n is the full original number. Since 0 digits have been removed from n both count and n are accurate and the invariant holds.

```
def count_digits(n):
    count = 0
    while n > 0:
        n //= 10
        count += 1
    return count
```

Answer

- *Maintenance*: Suppose at the start of some iteration the invariant holds and count holds the number of digits already removed and n is the remaining portion of the original number, with the last count digits have been removed.
  - Once we enter the loop, we update `n=n//10`, removing the last digit, and increment `count = count+1` of removed digits by 1.
  - Thus, at the start of the next iteration, omore digit has been removed from n and the number of removed digits count has increased by 1. The invariant holds.

```
def count_digits(n):
    count = 0
    while n > 0:
        n //= 10
        count += 1
    return count
```

Answer

- *Post-condition*: The loop exits when n=0. By the invariant, we have count being the number of right-most digits that have been removed from the original number and n being the remaining portion of the original number. But since all the digits have been removed once n is 0, count will be equal to the total number of digits in the original number n.

```
def count_digits(n):
    count = 0
    while n > 0:
        n //= 10
        count += 1
    return count
```

Answer

- *Termination*: At each iteration, the statement n //= 10 strictly decreases. Since n is positive integer, this process can only happen a finite number of times (at most equal to the number of digits of n). Eventually, n becomes 0, making the guard n > 0 False, so the loop terminates.

```
def count_digits(n):
    count = 0
    while n > 0:
        n //= 10
        count += 1
    return count
```